

Technical Performance (100m):

Frequency (MHz)	RL \geq dB	ATT \leq dB	NEXT \geq dB	PHASE DELAY \leq ns	Frequency (MHz)	PSNEXT \geq dB	ELFEXT \geq dB	PSELFEXT \geq dB
1.0	20.0	2.0	78.0	570.0	1	75.0	78.0	75.0
4.0	23.0	3.74	78.0	552.0	4	75.0	78.0	75.0
8.0	24.5	5.24	78.0	546.7	8	75.0	75.9	72.9
10.0	25.0	5.86	78.0	545.4	10	75.0	74.0	71.0
16.0	25.0	7.41	78.0	543.0	16	75.0	69.9	66.9
20.0	25.0	8.29	78.0	542.0	20	75.0	68.0	65.0
25.0	24.3	9.29	78.0	541.2	25	75.0	66.0	63.0
31.25	23.6	10.41	78.0	540.4	31.25	75.0	64.1	61.1
62.5	21.5	14.88	75.5	538.6	62.5	72.5	58.1	55.1
100	20.1	19.02	72.4	537.6	100	69.4	54.0	51.0
150	18.9	23.56	69.8	536.9	150	66.8	50.2	47.2
200	18.0	27.47	67.9	536.5	200	64.9	48.0	45.0
250	17.3	30.97	66.4	536.3	250	63.4	46.0	43.0
300	17.3	34.19	65.2	536.1	300	62.2	44.5	41.5
600	17.3	50.10	60.7	535.5	600	57.7	38.4	35.4

